



ISOLMANT FASCIA PERIMETRALE TECNICA RETICOLATA

Adhesive bands in reticulated expanded closed-cell polyethylene for an easy "L" installation. These bands come with a screen-printed side with the installation instructions.

This product is available in three versions:

- h 18.5 cm (11 cm wall + 7.5 cm floor);
- h 25 cm (17.5 cm wall + 7.5 cm floor).



isolmantFasciaPRM

THICKNESS	Approx. 5 mm
FLANKING PATH NOISE REDUCTION	The non-use of Isolmant Fascia Perimetrale causes an acoustic bridge and a consequent decibel loss
INSTALLATION	<ul style="list-style-type: none"> • After removing the protection film of the adhesive side, Isolmant Fascia Perimetrale can be installed on the floor (or the resilient layer already positioned) and then to the wall • The extra length could be trimmed with "snap-off blade" utility knife after completing flooring installation and finishing
SIZE	Strips of 18.5 - 25 cm x 50 m
PACKAGING	Version h 18.5 cm: 8 strips (equal to 400 m) Version h 25 cm: 6 strips (equal to 300 m)

→ Conditions of use

Isolmant Fascia Perimetrale avoids flanking noise and vibration transmission from floating screed to the partition wall. To ensure the proper functioning of the floating floor it is necessary that the whole system resting on the resilient layer can move freely. Flanking strips avoid any rigid contacts between screed and walls, pillars and façades. In addition, as an alternative to turn up and bend the resilient layer along the edges of the floating screed (which is sometimes difficult during installation), it is possible to apply Isolmant flanking strips along the room perimeter. It can substitute the elastic material used for expansion joints. Designed for easy installation, this flanking strip ensures an high-level of acoustic performance.

To ensure the good functioning of the floating floor, it is also essential to insulate the vertical surfaces of the flooring screed. To do this, as an alternative to the "fold" of the resilient layer, often difficult during construction, it is sufficient to apply Isolmant Fascia Perimetrale to the foot of the wall and around the perimeter.

→ Item specifications

Perimeter flanking strip made of expanded closed-cell cross-linked polyethylene with approx. 30 density kg/m³. This product is designed for easy installation. These strips come with a screen-printed side with installation instructions. Height 18.5 cm or 25 cm, pack of 8 or 6 rolls of 50 m/each. Thickness approx. 5 mm.

WARNING: This technical data sheet is not a valid specification and, if it consist of multiple pages, be sure to read the full document. This instruction are the best of our current experience but are indicative information. Assuming the liability resulting from the use of this product, it is up to the user to establish whether the product is suitable for the intended use.

isolmant by TECNASFALTI